

YOUR FACTORY IS UNDER OUR WARRANTY

insulating glass production machinery

GLASS MACHINERY

www.lidermachine.com



VERTICAL GLASS WASHING MACHINE

**DIKEY CAM YIKAMA
MAKİNESİ**



SERIES

AQUA

WASHING MACHINE

- 1700 / 4 BRUSHES
- 1700 / 6 BRUSHES
- 2000 / 6 BRUSHES
- 2500 / 6 BRUSHES

VERTICAL GLASS WASHING MACHINE

MAKİNE ÖZELLİKLERİ

Ana Yıkama Ünitesi paslanmaz çelik
2 adet ısıtıcı, paslanmaz çelik Su Tankı
Ana Yıkama Ünitesinde ve Su Tankında durulama bölümü
Cam yürütmede hız kontrolü
Giriş ve Çıkış Ünite tekerlekleri otomatik hareketli
Kolay ayarlanabilen dijital göstergeli sıcaklık kontrolü
Maksimum uzunlukta (3 metreye kadar)cam yıkayabilme özelliği
Yüksek hassasiyetli 4 fırça veya 6 fırça
2 – 10 mm yıkanabilir cam kalınlığı
Ayarlanabilir fırça mesafesi
Kaplama (Low-E) cam yıkayabilen yüksek hassasiyetli fırçaları
“Düşük Su Seviyesi” uyarı sistemi
7,5 kW kurutma fanı
Kesilmeye ve aşınmaya dayanıklı konveyör tekerlekleri
Yıkanmış camlardaki temizlik kalitesini gösteren aydınlatmalı ünite
Soldan sağa çalışma yönü
Uzun ömürlü koruma için elektrostatik fırın boya
Güvenlik koşullarına uygun elektrik sistemi

MACHINE FEATURES

Main Washing Unit stainless steel
Stainless steel Water Tank with 2-piece heater
Flushing section in Main Washing Unit and Water Tank
Speed Adjustment on glass propulsion
Automatic propulsion on Entry and Exit Units' conveyors
Temperature control with easy adjustable digital indicator
Glass Washing on Maximum Length (Up to 4 m.)
High sensitive 4 brushes and 6 brushes
Standard series 2 – 10 mm washable glass thickness
Adjustable brush range
High sensitive brushes for washing Low-e
Warning system for “Low Level Water”
7,5 kW drying fan
Durable conveyors against cutting and wearing out
Illumination Unit for showing quality on washed glasses
Operation direction from left to right
Electrostatic powder paint for long-life protection

Model		AUQA 1700/4F	AUQA 1700/6F	AUQA 2000/6F	AUQA 2500/6F	
Length	Uzunluk	6900 mm	7200 mm	7200 mm	8600 mm	
Height	Yükseklik	2800 mm	2800 mm	3200 mm	3300 mm	
Width	Genişlik	1800 mm	1800 mm	1800 mm	1800 mm	
Weight	Ağırlık	1700 kg	1800 kg	2100 kg	2600 kg	
Washable Glass Dimensions	Min (mm)	Yıkanabilir cam ölçüsü	120x350	120x350	120x350	120x350
	Max (mm)		1700x2400	1700x2400	2000x2400	2500x3000
Washable Glass Thickness	Min (mm)	Yıkanabilir cam kalınlığı	3	3	3	3
	Max (mm)		10	10	10	10
Noise Emission Level	Gürültü şiddeti	75 dB(A)	75 dB(A)	75 dB(A)	90 dB(A)	
Air Consumption	Hava tüketimi	370 lt/min.	370 lt/min.	370 lt/min.	370 lt/min.	
Water Tank Capacity	Su tankı kapasitesi	120 lt	160 lt	160 lt	200 lt	
Total Power	Toplam Güç	11 Kw	12 Kw	12 Kw	19,5 Kw	
Voltage	Voltaj	400 V 3 NPE AC				
Frequency	Frekans	50 Hz.				

AQUA

OPSİYON

- ÇALIŞMA YÖNÜ SAĞDAN SOLA
- 8 FIRÇALI YIKAMA ÜNİTESİ
- INOX YIKAMA GÖVDESİ

OPTIONS

- Operation direction from right to left
- 8 brushed Washing Unit
- INOX washing body

10 YEARS OF EXPERIENCE



LIDER Glass Machinery;

automatic glass cutting machine, automatic glass cutting line, digital glass cutting table, manual glass cutting table, automatic combination glass washing line double and triple glass production, automatic combination glass washing line facade glass production machine, standard glass washing machine, economic glass washing machine , servo controlled glass washing machine, silicone bonding glass putty extruder, polysulfide thiocol extruder, polyurethane glass putty extruder, hotmelt extruder machine, manual press table, Frezer freezer, standard rotary table, manual batten cutting machine, dehumidifier filling machine, automatic batten bending We manufacture machines with alternative solutions for the production of insulated glass, automatic dehumidifier filling machine, and heat insulated glass.

As LIDER Machine, we continue to produce innovative and technological heat insulated glass machines with our own designs of our research and development studies that we do in line with the wishes of our customers. We are always developing, growing and producing with our understanding of high quality production.



+90 262 504 78 70



info@lidermachine.com
onder@lidermachine.com



www.lidermachine.com



Çerkesli OSB İmes San.Sit. 10.Cad. No:4
Dilovası /KOCAELİ /TÜRKİYE

lider.cammakina



liderglassmachine



lidermachine



lider glass machinery



lider glass machinery



+90 (532) 400 70 70



www.lidermachine.com