

YOUR FACTORY IS UNDER OUR WARRANTY

*insulating glass production machinery*

# GLASS MACHINERY

[www.lidermachine.com](http://www.lidermachine.com)





# Butyl Extruder

**BUTİL EKSTRUDER MAKİNESİ**



# HOTBAR

HOT INSULATION

sıcak izolasyon

**7**  
**KG**



# BUTYL EXTRUDER MACHINE

## MAKİNE ÖZELLİKLERİ

5.7" Renkli dokunmatik ekran  
Tek Tuş Kullanım Kolaylığı – Programlanabilir otomatik çalışma seçenekleri (Bant hızı, baskı tekeri kalkış/iniş süreleri, malzeme başlangıç/bitiş süreleri)  
Otomatik veya manuel kullanım seçeneği  
7 kg. lık malzeme haznesi  
Otomatik açma/kapama sağlayan zamanlama sistemi  
Farklı profil kalınlıklarında kullanım seçeneği ( 6 mm.den 20 mm.ye kadar ayarlanabilir)  
Malzeme çekme hızı 10 m/dk.'dan 40 m/dk. ya ayarlanabilir  
Dokunmatik ekrandan kolay ayarlanabilir Sıcaklık Kontrol Sistemi (Tank ve Nozul Sıcaklığı)  
Ayarlanabilir malzeme akış oranı  
Aşınmaya ve ısınmaya karşı dayanıklı taşıyıcı bant  
Hava tahrikli hidrolik pompa ile çalışma nedeniyle enerji tasarrufu (yaklaşık 2 kW)  
Maksimum 35 dakika içerisinde, malzemeyi ısıtıp çalışmaya hazır konuma geçerek zaman kazancı  
PID ısı kontrol sistemi sayesinde hassas sıcaklık ölçümü  
Kolay ayarlanabilir pnömatik kontrollü hidrolik çalışma basıncı  
Düşük sıcaklık emniyet sistemi  
Malzeme değişiminde tehlike önleyici kapak emniyet siviçi

## Opsiyonlar:

İsteğe bağlı olarak dairesel ve kemer şekilli profillere butil çekebilme özelliği  
İsteğe bağlı olarak eklenebilir bantlama ünitesi (Bantlama ünitesi ile dakikada 80 m.ye kadar)

## Mechnical Specifications

5.7" colorful touch screen  
Easy One-Button Operating -Programmable 8 automatic operating options (Conveyer strip speed, clamp down/up time, material start/stop time)  
Automatic or manuel operating options  
7 kg. material capacity  
Timing system that provides automatic turn on/off  
Operating options in different profile thicknesses (Adjustable from 6 mm. to 20 mm. )  
Material injection possibility in minutes from 10m. to 55m.  
Easy Temperature control system on Touch Screen (Adjustable tank and nozzle temperature)  
MONOFAZE (220 V) electric requires  
Adjustable material flow-rate  
Conveyor strip is resistant to warm-up and deprecation  
Energy saving (nearly 2 kW) due to air propulsion hydraulic pump  
Time saving due to heating material and ready to work maximum in 35 minutes  
Sensitive temperature calculating because of PID control system  
Easy adjustable pneumatic controlled hydraulic working pressure  
Low temperature safety system  
Cover safety switch while putting material to tank  
Electrostatic powder paint for long-life protection  
Electrical system that is suitable for general security conditions

## Option :

Butyl-withdrawal feature of circular and arch-shaped profiles upon request  
Optional banding unit (up to 80 m / min with banding unit)

Model		HOTBAR
L = TOTAL LENGTH	Uzunluk	3000 mm
H = TOTAL HEIGHT	Genişlik	1200 mm
W = TOTAL WIDTH	Yükseklik	600 mm
TOTAL WEIGHT	Ağırlık	550 kg
TOTAL POWER	Toplam Güç	3,5 kW
VOLTAGE	Gerilim	400 V 3 NPE AC
FREQUENCY	Frekans	50 Hz
HYDRAULIC PUMP CAPACITY	Hidrolik Pompa Kapasitesi	6 lt/dk.
MAX. HYDRAULIC PRESSURE	Max.Çalışma Basıncı	200 bar
WORKING HYDRAULIC PRESSURE	Optimum Çalışma Basıncı	100-150 bar
OIL STORAGE CAPACITY	Hidrolik Yağ Tankı Kapasitesi	18 litre
WORKING PROFILE THICKNESS RANGE	İşlenebilen Profil Kalınlığı	6-20 mm
MATERIAL TANK CAPACITY	Malzeme Tankı Kapasitesi	7 kg
AIR PRESSURE	Hava Basıncı	6 bar
AIR CONSUMPTION	Hava Tüketimi	10 lt/dk
NOISE LEVEL OF EMISSIONS	Gürültü şiddeti	70 dB (A)

7  
KG



## 10 YEARS OF EXPERIENCE



LIDER Glass Machinery;

automatic glass cutting machine, automatic glass cutting line, digital glass cutting table, manual glass cutting table, automatic combination glass washing line double and triple glass production, automatic combination glass washing line facade glass production machine, standard glass washing machine, inox body glass washing machine , servo controlled panell pressing glass washing machine, silicone bonding extruder, polysulfide thiocol extruder, polyurethane extruder, hotmelt extruder machine, manual press table, Frezer, standard rotary table, manual cutting machine, desiccant filling machine, automatic bending machine We manufacture machines with alternative solutions for the production of insulated glass, automatic desiccant filling machine and heat insulated glass.

As LIDER Machine, we continue to produce innovative and technological heat insulated glass machines with our own designs of our research and development studies that we do in line with the wishes of our customers. We are always developing, growing and producing with our understanding of high quality production.



+90 262 504 78 70



info@lidermachine.com  
onder@lidermachine.com



www.lidermachine.com



Çerkesli OSB İmes San.Sit. 10.Cad. No:4  
Dilovası /KOCAELİ /TÜRKİYE

lider.cammakina



liderglassmachine



lidermachine



lider glass machinery



lider glass machinery



+90 (532) 400 70 70



www.lidermachine.com